



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 46



PRODUCT DATA SHEET



Radial

E-4

B

238

Technologies



All Steel

Performance



Hard Rocky Surface



Traction



Stability



Durability



EARTHMAX SR 46
RADIAL OTR TIRES

🇬🇧 EARTHMAX SR 46 for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tire has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tire life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity. EARTHMAX SR 46 features a special lug block pattern with circumferential groove to optimize the cornering performance with minimum tread face damage.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM		
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.	
Ø 49"	27.00 R 49	TL	E-4	**	223 B	CRC	455	746	2688	1225	8165	68	19.50/4.0	-	
	27.00 R 49	TL	E-4	**	223 B	STD	590	746	2688	1225	8165	68	19.50/4.0	-	
	27.00 R 49	TL	E-4	**	223 B	HRC	655	746	2688	1225	8165	68	19.50/4.0	-	
Ø 51"	30.00 R 51	TL	E-4	**	230 B	CRC	500	835	2895	1300	8800	77	22.00/4.5	-	
	30.00 R 51	TL	E-4	**	230 B	STD	610	835	2895	1300	8800	77	22.00/4.5	-	
	30.00 R 51	TL	E-4	**	230 B	HRC	725	835	2895	1300	8800	77	22.00/4.5	-	
	33.00 R 51	TL	E-4	**	235 B	CRC	558	905	3050	1401	9377	87	24.00/5.0	-	
	33.00 R 51	TL	E-4	***	238 B	CRC	612	905	3050	1401	9377	87	24.00/5.0	-	
	NEWSIZE														
	33.00 R 51	TL	E-4	**	235 B	STD	697	905	3050	1401	9377	87	24.00/5.0	-	
33.00 R 51	TL	E-4	**	235 B	HRC	800	905	3050	1401	9377	87	24.00/5.0	-		

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference