



IS standard



GROWING TOGETHER

# AGRIMAX *Pro*CROP



PRODUCT DATA SHEET



Radial



# AGRIMAX PROCROP

**UK** AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops. The lug block design of AGRIMAX PROCROP is optimized to enhance traction on less compact soils, such as sandy or freshly plowed fields. This feature allows the tire to perform effectively in challenging conditions, ensuring excellent grip and reducing the risk of slippage. On asphalt, good roadability is guaranteed by the closed tread center and the strong sidewall that gives high lateral stability while travelling on the road. AGRIMAX PROCROP ensures superior performance even at high speed of 65 km/h. The strong polyester structure of the tire provides improved durability, better handling as well as dimensional stability enhancing vehicle stability and control. The steel belts offer excellent puncture resistance.

**Technologies**



VF Technology



Larger Footprint



High Speed



Steel Belted



Strong Casing

**Performance**



Reduced Soil Compaction



Field Protection



High Load Capacity



Stability



Traction



Self-Cleaning



Durability



Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 32"	VF 270/95 R 32	148 D	W 9	-	280	1339	618	4056	650	SB
Ø 36"	VF 270/95 R 36	150 D	W 9	-	280	1441	665	4393	700	SB
Ø 38"	VF 270/95 R 38	151 D	W 9	-	280	1491	695	4541	725	SB
Ø 46"	VF 320/90 R 46 CFO	165 D	DW 11	W 11 ; DW 10	323	1750	817	5345	825	SB
	<b>NEWSIZE</b>									
Ø 48"	VF 230/95 R 48	148 D	W 8	W 7	233	1660	785	5100	800	SB
	<b>NEWSIZE</b>									
	VF 270/95 R 48	155 D	W 9	-	280	1745	815	5330	850	SB
Ø 54"	VF 270/95 R 54	157 D	W 9	-	280	1900	895	5830	925	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index