



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenge of both technology and performance for modern tractors. This tire is perfect for soil tillage and haul applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires at high speeds. It also features the Narrow Rim Option, which allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance drive performance both in the fields and on the road reducing fuel consumption.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor



Version

SPECIAL

Tire Type

TL

Tyre size

580/85R46

LI/SS

179;D

## Dimensions IS Standard

SW (IS) (mm)	605
OD (IS) (mm)	2156
SLR (IS) (mm)	947
RC (IS) (mm)	6451
ECE	E11-106R-0011691
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2										
70	3530	4095	4660	5295	5860	6425	7055										
from 65 to 40	3875	4495	5115	5815	6435	7055	7750										
30	3955	4585	5220	5930	6565	7195	7905										
20	4030	4675	5320	6045	6690	7335	8060										
10	4265	4945	5630	6395	7080	7760	8525										
10HT	3955	4585	5220	5930	6565	7195	7905										
Upto 10 Cyc	5755	6680	7600	8635	9555	10475	11510										
Upto 15 Cyc	5255	6095	6935	7880	8720	9560	10505										
Upto 30 Cyc	4400	5105	5810	6600	7305	8010	8800										

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. No one is permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, or in any format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..