



FLOTATION TR 675



Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Tractor

Version

STANDARD

Tire Type

TL

Tyre size

550/45-22.5

LI/SS

Dimensions IS Standard

SW (IS) (mm)	543
OD (IS) (mm)	1070
Rim Rec	AG 16.00
ECE	E4-106R-002723

Load Capacity (IS)

km/h / bar	03:00:00	03:50:00	04:00:00																	
10 FR	6270	6860	7420																	
20 FR	5645	6175	6680																	
30 FR	5020	5490	5935																	
40 FR	4480	4900	5300																	
50 FR	4030	4410	4750																	
10 DW	4440	4860	5250																	
20 DW	3995	4370	4725																	
30 DW	3550	3885	4200																	
40 DW	3170	3470	3750																	
50 DW	2855	3125	3350																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

