



SKID POWER HD (A)



Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

UM

US Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Skid Steer

Version	IMPLEMENT
Tire Type	TL
Tyre size	14-17.5
LI/SS	140;A8

Dimensions US Standard

USA Code	94056071
SW (US) (in)	13.8
OD (US) (in)	36.6
SLR (US) (in)	16.5
RC (US) (in)	108.0
Rim Rec	10.50

Load Capacity (US)

mph / psi	80
25	5520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..