



TR 315

Description

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.

UM

US Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Implement Machinery



Version

STANDARD

Tire Type

TL

Tyre size

x15.50-15

LI/SS

Dimensions US Standard

USA Code	94022441
SW (US) (in)	15.4
OD (US) (in)	31.5
SLR (US) (in)	13.9
RC (US) (in)	91.3
Rim Rec	13 LB
ECE	E4-106R-002208

Load Capacity (US)

mph / psi	45
30	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..