



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF520/85R42
LI/SS	180;D

## Dimensions US Standard

USA Code	94067237
SW (US) (in)	21.1
OD (US) (in)	76.8
SLR (US) (in)	34.5
RC (US) (in)	230.0
Rim Rec	DW 18 L
ECE	E11-106R-007169
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35	46
<b>45</b>	6260	7390	8510	9480	10590	11560	12690	13650	16050
<b>from 40 to 25</b>	6880	8110	9350	10410	11640	12700	13930	14990	17640
<b>20</b>	7020	8280	9530	10610	11880	12960	14220	15300	17990
<b>12</b>	7150	8440	9720	10820	12110	13220	14490	15600	18340
<b>5</b>	7570	8930	10280	11450	12810	13980	15330	16490	19400
<b>Upto 5 Cyc with front loader</b>	9630	11360	13090	14570	16300	17780	19510	20990	24690
<b>5 HT</b>	7020	8280	9530	10610	11880	12960	14220	15300	17990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..