



## EARTHMAX SR 53



### Description

EARTHMAX SR 53 is an All Steel radial tire suitable for use on loaders, dozers and low profile dump trucks in severe rocky conditions, including underground mines and yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent performance in the case of underground mine application, consult your distributor or BKT representative.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Dozer

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	35/65R33
LI/SS	224;A2

## Dimensions IS Standard

OD (IS) (mm)	2063
SLR (IS) (mm)	915
RC (IS) (mm)	6215
Rim Rec	28.00/3.5
TRA Code	L5

## Load Capacity (IS)

km/h / bar	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00													
10	23600	25000	25750	26500	27250	28000													

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..