



US standard



GROWING TOGETHER

EM 937 E3 (L)



PRODUCT DATA SHEET



Bias



EM 937 E3 (L)

EM 937 (E-3/L-3) has been specially designed for loaders and backhoe loaders in dig and load applications, depending on the size. It features excellent durability and provides cut and chip resistance.

Performance



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 24"	94015337	14.00 - 24	TT	20	-	STD	53.9	14.8	24.7	159.4	33	29	10.00 W	-
	94015344	14.00 - 24	TL	20	-	STD	53.9	14.8	24.7	159.4	33	30	10.00 W	-
	94015351	14.00 - 24	TT	24	-	STD	53.9	14.8	24.7	159.4	33	31	10.00 W	-
	94015368	14.00 - 24	TL	24	-	STD	53.9	14.8	24.7	159.4	33	32	10.00 W	-
	94030118	14.00 - 24	TT	28	-	STD	53.9	14.8	24.7	159.4	33	31	10.00 W	-
	94015375	14.00 - 24	TL	28	-	STD	53.9	14.8	24.7	159.4	33	32	10.00 W	-
	94041336	14.00 - 24	TT	32	-	STD	53.9	14.8	24.7	159.4	33	33	10.00 W	-
	94015382	14.00 - 24	TL	32	-	STD	53.9	14.8	24.7	159.4	33	34	10.00 W	-
Ø 25"	94040421	14.00 - 25	TT	12	-	STD	53.9	15.4	24.4	161.6	33	24	10.00/1.5	-
	94015399	14.00 - 25	TT	20	-	STD	53.9	14.8	24.4	161.6	33	29	10.00/1.5	-
	94015405	14.00 - 25	TL	20	-	STD	53.9	14.8	24.4	161.6	33	30	10.00/1.5	-
	94015429	14.00 - 25	TT	24	-	STD	53.9	14.8	24.4	161.6	33	31	10.00/1.5	-
	94015436	14.00 - 25	TL	24	-	STD	53.9	14.8	24.4	161.6	33	31	10.00/1.5	-
	94048939	14.00 - 25	TT	20	-	AB	53.9	14.8	24.4	161.6	33	29	10.00/1.5	-
	94050734	14.00 - 25	TT	20	-	A + SB	53.9	14.8	24.4	161.6	33	30	10.00/1.5	-
	94048922	14.00 - 25	TT	20	-	SB	53.9	14.8	24.4	161.6	33	30	10.00/1.5	-

STD: Standard - AB: Aramid Belted - A+SB: Aramid + Steel Belted - SB: Steel Belted

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference