



US standard



GROWING TOGETHER

# FL 637



PRODUCT DATA SHEET



Radial



# FL 637

FL 637 is a radial flotation tire suitable for spreaders, trailers and tankers. The reinforced bead structure provides enhanced durability and higher load capacity. In addition to excellent flotation features leading to reduced soil compaction, this tire shows outstanding self-cleaning properties. The directional tread design ensures excellent traction and enabling speeds up to 70 km/h.

### Technologies



Reinforced Bead



High Speed

### Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 17"	94054909	520/50 R 17	151 D/ 148 E	16.00	-	20.3	37.5	16.3	115.4	20	134	STD
Ø 22.5"	94074174	560/45 R 22.5	160 D	AG 16.00	-	21.4	42.4	19.7	130.9	27	233	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference