



## AT 171

### Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

### UM

IS Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ ATV



Version	STANDARD
Tire Type	TT
Tyre size	35x9-20
LI/SS	85;A8

## Dimensions IS Standard

SW (IS) (mm)	200
OD (IS) (mm)	895
SLR (IS) (mm)	419
RC (IS) (mm)	2670
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

## Load Capacity (IS)

km/h / bar	1.40	1.00
40 MUD BOGGING	515	-
80 MUD BOGGING	257	-
40 CASUAL TRANSPORT	-	425
80 CASUAL TRANSPORT	-	218

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..