



IS standard



GROWING TOGETHER

# RIDEMAX

RADIAL TRANSPORT TIRES

## FL 615



PRODUCT DATA SHEET



Radial



D



200

**Technologies**



Steel Belted



Rounded Shoulder Technology

**Performance**



Reduced Soil Compaction



Self-Cleaning



High Load Capacity



Ideal for grassland



Low Rolling Resistance



**RIDEMAX FL 615**

RADIAL TRANSPORT TIRES

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 32"	800/65 R 32	185 D	DW 27 B	-	830	1853	834	5624	875	SB
	VF 800/65 R 32	190 D	DW 28 B	-	815	1850	811	5610	875	SB
Ø 38"	VF 900/65 R 38	200 D	DW 30 B	-	891	2115	929	6445	975	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index