



## LOADER PLUS



### Description

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suits best for loading and dozing operations.

### UM

IS Standard

### Construction

### Machinery

Industrial & Construction ■ Loader,OTR ■ Loader

Version	STANDARD
Tire Type	TT
Tyre size	17.5-25
LI/SS	

## Dimensions IS Standard

OD (IS) (mm)	1345
SLR (IS) (mm)	622
RC (IS) (mm)	3980
Rim Rec	14.00/1.5
TRA Code	L3

## field\_1

km/h / bar	4.75
10	7300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..