



US standard



GROWING TOGETHER

STEER GRIP



PRODUCT DATA SHEET



Bias



STEER GRIP

STEER GRIP is the perfect steering-axle fitment for on/off trucks. The wide central rib with straight lugs makes the tire suitable for free rolling applications and provides enhanced grip for excellent performance on both wet and dry conditions off the road. The special tread compound has been designed for combining best wear resistance with cut-and-chip resistance whereas the strong casing ensures an extended tire life-cycle.

Performance



Durability



Heavy Duty



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 20"	94047024	10.00 - 20	TT	18	-	STD	-	-	42.7	11.3	20.1	129.5	26	136	7.5	7.0
	94052103	11.00 - 20	TT	18	-	STD	-	-	44.1	11.8	20.7	133.7	29	148	8.0	7.5
Ø 24"	94049363	12.00 - 24	TT	20	-	STD	-	-	49.1	12.2	23.1	149.0	28	191	8.5	8.0

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference