



EARTHMAX SR 47



Description

EARTHMAX SR 47 (E-4) operating in conditions of high load, high tread depth and the unique tread pattern, reducing downtime and fuel consumption.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	STANDARD COMPOUND
Tire Type	TL
Tyre size	18.00R33undefined
LI/SS	191;B

Dimensions IS Standard

OD (IS) (mm)	1885
SLR (IS) (mm)	867
RC (IS) (mm)	5674
Rim Rec	13.00/2.5
TRA Code	E4

Load Capacity (IS)

km/h / bar	05:00:00	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00	07:15:00
50	8500	8750	9000	9250	9750	10000	10300	10600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 21-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. and its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The product name and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. No part of this publication may be reproduced, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or any other format without the prior written consent of Balkrishna Industries Ltd..