



ROCK GRIP E4



Description

ROCK GRIP (E-4) is a bias-ply tire specially designed for haul trucks in mining service and quarry operations. Whenever your short-haul site conditions require both heat resistance and cut protection, ROCK GRIP is the tire you can rely upon.

UM

US Standard

Construction

 Bias

Machinery

OTR ■ Rigid Dump Truck

Version STANDARD

Tire Type TL

Tyre size 21.00-35

LI/SS

Dimensions US Standard

USA Code	94015580
OD (US) (in)	80.3
SLR (US) (in)	37.1
RC (US) (in)	238.9
Rim Rec	15.00/3.0
TRA Code	E4

Load Capacity (US)

mph / psi	80	109
30	28300	-
5	-	50700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..