



US standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 765



PRODUCT DATA SHEET



Radial



AGRIMAX RT 765

RADIAL TRACTOR TIRES



🇺🇸 AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 16"	94026869	200/70 R 16	94 A8/B	W 6	-	7.8	27.0	12.4	81.1	32	34	STD
	94045365	220/70 R 16	99 A8/B	W 7	W 8	8.7	28.1	12.8	84.4	35	41	STD
	94022014	240/70 R 16	104 A8/B	W 8	W 8 L; W 9 L	9.6	29.2	13.2	85.7	36	45	STD
	94021888	260/70 R 16	109 A8/B	W 8	W 8 L; W 9 L	10.2	30.3	13.6	89.9	37	50	STD
	94021895	280/70 R 16	112 A8/B	W 9	W 8; W 8 L; W 10	11.1	31.4	14.0	93.3	40	58	STD
Ø 18"	94021901	280/70 R 18	114 A8/B	W 9	W 8; W 10	10.8	33.4	15.0	100.3	40	62	STD
Ø 20"	94030576	260/70 R 20	113 A8/B	W 8	9; W 9	10.2	34.3	15.8	103.9	37	60	STD
	94044221	260/70 R 20	113 A8/B	W 8	9; W 9	10.2	34.3	15.8	103.9	37	57	SPL
	94021970	280/70 R 20	116 A8/B	W 9	W 8; W 10	10.8	35.4	16.1	106.5	40	68	STD
	94044238	280/70 R 20	116 A8/B	W 9	W 8; W 10	10.8	35.4	16.1	106.5	40	64	SPL
	94021925	300/70 R 20	120 A8/B	W 9	W 10	11.6	37.5	16.9	112.4	41	77	STD
	94021932	320/70 R 20	123 A8/B	W 10	W 9; W 11	12.6	38.7	17.5	115.7	41	86	STD
	94021949	360/70 R 20	129 A8/B	W 11	W 10; W 12	14.1	41.0	18.5	122.9	51	117	STD
	94021987	380/70 R 20	132 A8/B	W 12	W 11; W 13	15.0	42.6	19.0	126.5	52	130	STD

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 24"	94063031	320/70 R 24	116 D	W 10	W 9 ; W 11	12.6	43.1	19.8	127.8	50	104	STD
	94063154	320/70 R 24	116 D	W 10	W 9 ; W 11	12.6	43.1	19.8	127.8	50	105	SPL
	94063017	360/70 R 24	122 D	W 11	W 10 ; W 12	14.1	45.4	20.4	133.7	51	134	STD
	94063130	360/70 R 24	122 D	W 11	W 10 ; W 12	14.1	45.4	20.4	133.7	51	134	SPL
	94062607	380/70 R 24	125 D	W 12	W 11 ; W 13	15.0	46.9	21.2	140.2	52	144	STD
	94062614	380/70 R 24	125 D	W 12	W 11 ; W 13	15.0	46.9	21.2	140.2	52	145	SPL
	94063024	420/70 R 24	130 D	W 13	W 12 ; W 14 L	16.5	49.1	21.8	144.9	55	176	STD
	94063147	420/70 R 24	130 D	W 13	W 12 ; W 14 L	16.5	49.1	21.8	144.9	55	177	SPL
	94063260	420/70 R 24	134 D	W 13	W 12 ; W 14 L	16.5	49.1	21.8	144.9	55	176	STD
	94063277	420/70 R 24	134 D	W 13	W 12 ; W 14 L	16.5	49.1	21.8	144.9	55	177	SPL
94062195	480/70 R 24	138 D	W 15 L	W 14 L ; W 16 L	18.9	51.8	23.0	153.5	61	220	STD	
94062270	480/70 R 24	138 D	W 15 L	W 14 L ; W 16 L	18.9	51.8	22.8	153.3	61	218	SPL	
Ø 28"	94063048	360/70 R 28	125 D	W 11	W 10 ; W 12	14.1	49.3	22.8	148.3	51	150	STD
	94063161	360/70 R 28	125 D	W 11	W 10 ; W 12	14.1	49.3	22.8	148.3	51	151	SPL

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 28"	94063055	380/70 R 28	127 D	W 12	W 11 ; W 13	15.0	50.9	23.1	152.9	52	162	STD
	94063178	380/70 R 28	127 D	W 12	W 11 ; W 13	15.0	50.9	23.1	152.9	52	162	SPL
	94062171	420/70 R 28	133 D	W 13	W 12 ; W 14 L	16.5	53.1	23.8	158.3	55	195	STD
	94062263	420/70 R 28	133 D	W 13	W 12 ; W 14 L	16.5	53.1	23.8	158.3	55	194	SPL
	94062201	480/70 R 28	140 D	W 15 L	W 14 L ; W 16 L	18.9	55.9	25.0	164.8	61	245	STD
	94062287	480/70 R 28	140 D	W 15 L	W 14 L ; W 16 L	18.9	55.9	25.0	164.8	61	242	SPL
	94067251	600/70 R 28	157 D	DW 18 L	DW 20 B	23.3	61.1	27.4	184.7	72	375	STD
Ø 30"	94063062	420/70 R 30	134 D	W 13	W 12 ; W 14 L	16.5	55.0	24.8	164.3	55	209	STD
	94063185	420/70 R 30	134 D	W 13	W 12 ; W 14 L	16.5	55.0	24.8	164.3	55	210	SPL
	94062218	480/70 R 30	141 D	W 15 L	W 14 L ; W 16 L	18.9	58.2	25.9	172.1	62	254	STD
	94062294	480/70 R 30	141 D	W 15 L	W 14 L ; W 16 L	18.9	58.2	25.9	172.1	62	257	SPL
	94062256	600/70 R 30	152 D	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.0	188.0	72	378	STD
	94062331	600/70 R 30	152 D	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.0	188.0	72	380	SPL
Ø 34"	94062225	480/70 R 34	149 D	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.0	187.9	62	285	STD

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 34"	94062300	480/70 R 34	149 D	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.0	187.9	62	285	SPL
	94063109	480/70 R 34	155 D	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.7	188.5	62	300	STD
	94063284	480/70 R 34	155 D	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.7	188.5	62	302	SPL
	94063079	520/70 R 34	148 D	W 16 L	W 15 L ; W 18 L	20.3	64.6	29.1	194.0	67	334	STD
	94063192	520/70 R 34	148 D	W 16 L	W 15 L ; W 18 L	20.3	64.6	29.1	194.0	67	334	SPL
Ø 38"	94063086	480/70 R 38	145 D	W 15 L	W 14 L ; W 16 L	18.9	66.2	30.1	199.0	62	304	STD
	94063208	480/70 R 38	145 D	W 15 L	W 14 L ; W 16 L	18.9	66.2	30.1	199.0	62	306	SPL
	94062232	520/70 R 38	150 D	W 16 L	W 15 L ; W 18 L	20.3	68.9	31.2	208.7	67	366	STD
	94062317	520/70 R 38	150 D	W 16 L	W 15 L ; W 18 L	20.3	68.9	31.2	208.7	67	368	SPL
	94062249	580/70 R 38	155 D	W 18 L	-	22.7	71.9	32.3	215.4	72	454	STD
	94062324	580/70 R 38	155 D	W 18 L	-	22.7	71.9	32.3	215.4	72	459	SPL
	94038510	580/70 R 38	180 A8	W 18 L	-	22.7	71.9	32.3	216.7	72	536	SB
	94075133	580/70 R 38	180 D	W 18 L	DW 18 L ; DD 18 L	22.7	71.9	32.3	216.7	72	528	SB
	94063482	620/70 R 38	170 D	DW 20 B	DW 18 L ; W 18 L	24.6	72.2	32.6	220.1	72	485	STD

STD: Standard - SPL: Special - SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 38"	94063567	620/70 R 38	170 D	DW 20 B	DW 18 L ; W 18 L	24.6	72.2	32.6	220.1	72	487	SPL
	94063895	650/75 R 38	169 D	DW 21 B	DW 20 B ; DW 23 B	25.8	76.4	34.4	229.1	73	551	STD
	94066773	710/70 R 38	166 D	DW 23 B	-	28.2	77.1	33.8	226.4	74	632	STD
	94063222	710/70 R 38	166 D	DW 23 B	-	28.2	77.1	33.8	226.4	74	625	SPL
	94066797	710/70 R 38	171 D/ 174 A8	DW 23 B	-	28.2	77.1	33.8	226.4	74	672	STD
	94063499	710/70 R 38	175 D/ 178 A8	DW 23 B	-	28.2	77.1	33.8	226.4	74	661	STD
	94063536	710/70 R 38	175 D/ 178 A8	DW 23 B	-	28.2	77.1	33.8	226.4	74	666	SPL
Ø 42"	94063116	620/70 R 42	160 D	DW 20 B	DW 18 L	24.6	76.2	34.5	226.1	72	497	STD
	94063215	620/70 R 42	160 D	DW 20 B	DW 18 L	24.6	76.2	34.5	226.1	72	500	SPL
	94063505	620/70 R 42	166 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.4	72	507	STD
	94063543	620/70 R 42	166 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.4	72	510	SPL
	94063093	620/70 R 42	173 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.5	72	519	STD
	94063369	620/70 R 42	173 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.5	72	514	SPL
	94065493	650/75 R 42	170 D	DW 21 B	DW 20 B ; DW 23 B	25.8	80.4	36.1	242.0	73	601	STD

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



High Speed



Steel Belted

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 42"	94033157	710/70 R 42	173 D/ 176 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	719	STD
	94063512	710/70 R 42	176 D/ 179 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	712	STD
	94063550	710/70 R 42	176 D/ 179 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	717	SPL
Ø 46"	94063529	620/70 R 46	162 D	DW 20 B	-	24.6	80.2	36.4	240.4	72	559	STD
	94063574	620/70 R 46	162 D	DW 20 B	-	24.6	80.2	36.4	240.4	72	561	SPL

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference