



RIB 774 (C)

Description

RIB 774 (C) is a low-section and narrow-width implement tire. It is ideal for hay harvesting and transport applications with balers and trailers, both on- and off-the-road. It features great load capacity and a long tire life-cycle.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ■ Baler



Version	STANDARD
Tire Type	TL
Tyre size	215/75-17.5
LI/SS	

Dimensions US Standard

USA Code	94038084
SW (US) (in)	8.7
OD (US) (in)	30.5
SLR (US) (in)	14.2
RC (US) (in)	90.9
Rim Rec	6.75
ECE	E4-54R-0015341

Load Capacity (US)

mph / psi	131
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..