



AGRIMAX SPARGO

Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	VF380/90R46CFO
LI/SS	173;D

Dimensions US Standard

USA Code	94519231
SW (US) (in)	15.4
OD (US) (in)	72.9
SLR (US) (in)	33.3
RC (US) (in)	220.9
Rim Rec	DW 13 A
Rim Alt	W 13 A ; DW 12
ECE	E4-106R-000796
TRA Code	R1

Load Capacity (US)

mph / psi	14	12	20	23	26	29	32	35	38	41
45	5620	6270	7050	7700	8100	8480	8750	9010	9460	9930
from 40 to 25	6170	6880	7740	8460	8890	9320	9610	9890	10400	10900
20	6300	7030	7910	8640	9080	9510	9800	10090	10610	11120
12	6420	7160	8060	8800	9250	9690	9990	10290	10820	11340
5*	6780	7580	8530	9310	9780	10260	10580	10880	11440	11990
Upto 10 Cvc.	8610	9620	10820	11810	12420	13010	13420	13820	14510	15220
Upto 20 Cvc.	7210	8050	9050	9890	10400	10900	11240	11570	12150	12750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce,

transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..