



## AGRIMAX FORCE

### Description

AGRIMAX FORCE the high-end product of BKT is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester



Version	STANDARD
Tire Type	TL
Tyre size	IF710/60R38
LI/SS	172;D

## Dimensions IS Standard

SW (IS) (mm)	708
OD (IS) (mm)	1817
SLR (IS) (mm)	812
RC (IS) (mm)	5405
Rim Rec	DW 25 B
ECE	E11-106R-004754
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2630	3030	3490	3890	3450	4750	5325	5730
from 65 to 40	2895	3335	3840	4280	4785	5225	5855	6300
30	3010	3465	3990	4450	4975	5430	6085	6550
20	3125	3600	4145	4620	5165	5640	6320	6800
10	3675	4235	4875	5435	6075	6635	7435	8000
*Upto 10 Cyc with front loader	4050	4665	5375	5990	6695	7315	8195	8820
10 HT	3010	3465	3990	4450	4975	5430	6085	6550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..