



US standard



GROWING TOGETHER

AGRIMAX ELOS



PRODUCT DATA SHEET



Radial

R-2

B

178

Technologies



Extra Deep Tread

Performance



For muddy ground



Traction



Self-Cleaning



AGRIMAX ELOS

🇺🇸 AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 28"	94040810	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 13 ; W 14 L	17.2	57.8	26.2	171.2	95	283	STD
Ø 34"	94070299	480/70 R 34	155 A8/ 155 B	W 15 L	W 16 L ; W 14 L	19.7	63.2	28.9	191.7	96	363	STD
Ø 38"	94040452	340/85 R 38 (13.6 R 38)	133 A8/B	W 12	W 11	13.9	63.1	28.9	188.0	89	245	STD
	94036134	380/85 R 38 (14.9 R 38)	139 A8/B	W 12	W 11 ; W 13	15.0	65.4	30.4	196.6	93	297	STD
	94034512	420/85 R 38 (16.9 R 38)	144 A8/B	W 15 L	W 13 ; W 14 L	17.2	68.3	30.9	202.2	95	363	STD
	94053766	480/80 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 15 L ; DW 16 L	19.3	71.0	32.3	210.9	103	414	STD
	94058617	710/70 R 38	178 A8/B	DW 23 B	DW 25 B	28.2	79.5	36.0	240.3	114	777	STD
Ø 42"	94040827	480/80 R 42 (18.4 R 42)	151 A8/B	DW 16 L	DD 16 L ; W 16 L	19.3	74.4	33.7	221.6	102	459	STD
	94040834	520/85 R 42 (20.8 R 42)	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	35.6	230.9	107	550	STD
	94075850	520/85 R 42 (20.8 R 42)	167 A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	36.2	240.0	107	568	STD
Ø 46"	94070503	520/85 R 46	169 A8/ 169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W 18 L ; DD 16 L ; DD 18 L	20.9	81.7	37.7	247.8	106	622	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference