



IS standard



GROWING TOGETHER

# MULTIMAX

RADIAL MPT TIRES

## MP 540



PRODUCT DATA SHEET



Radial



**MULTIMAX MP 540**  
RADIAL MPT TIRES

**UK** MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability.

**Technologies**



Block Pattern



All Steel



M+S

**Performance**



Stability



Durability



High Load Capacity

	Tire size	Type	STAR RATING	LI/SS	Version	O.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 16"	315/55 R 16	TL	-	120 K/124 F	STD	305	751	354	2325	W 10 L	11
Ø 18"	335/80 R 18 (12.5 R 18)	TL	-	132 K	STD	340	985	446	3000	11	-
Ø 20"	275/80 R 20 (10.5 R 20)	TL	-	134 K	STD	270	955	443	2913	W 9	9
	335/80 R 20	TL	-	149 K	STD	340	1044	492	3258	11	-
	365/80 R 20 (14.5 R 20)	TL	-	152 K	STD	365	1086	495	3308	11	-
Ø 24"	405/70 R 20 (16.0/70 R 20)	TL	-	152 K	STD	402	1082	490	3295	13	12 ; 13 SDC
	405/70 R 24 (16.0/70 R 24) <b>NEWSIZE</b>	TL	-	152 J	STD	402	1174	530	3586	13	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference