



FORESTECH

Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Forwarder



Version STEEL BELTED

Tire Type TL

Tyre size 600/55-26.5

LI/SS 165;A8

Dimensions IS Standard

SW (IS) (mm)	610
OD (IS) (mm)	1335
SLR (IS) (mm)	618
RC (IS) (mm)	4032
Rim Rec	AG 20.00
ECE	E11-106R-003419
TRA Code	LS2

Load Capacity (IS)

km/h / bar	5.00
40	5150
30	5510
10	6300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..