



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 484



PRODUCT DATA SHEET



Radial

E-3

B

223

EARTHMAX SR 484

RADIAL OTR TIRES



EARTHMAX SR 484 is an All Steel radial tire specially designed for rigid dump trucks for transport in surface mining applications. It features a unique E-3 tread design with special tread compound ensures excellent protection in harsh and rocky conditions, together with enhanced traction and excellent self-cleaning properties. Its All Steel construction with multi-layer steel belts allows for superior protection against shocks, fatigue and rock drilling, enhancing uptime and increasing productivity. EARTHMAX SR 484 features a square shoulder design, which maximizes ground contact for excellent maneuverability and stability. This BKT tire is specially designed for higher speeds and long hauls.

Technologies



All Steel



Steel Belted



High Speed

Performance



Traction



Hard Rocky Surface



Self-Cleaning



Durability

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 49"	94067817	27.00 R 49	TL	**	223 B	CRC	E-3	360	104.2	28.9	47.0	317.1	60	2834	19.50/4.0	-
	94067824	27.00 R 49	TL	**	223 B	HRC	E-3	486	104.2	28.9	47.0	317.1	60	2820	19.50/4.0	-
	94067831	27.00 R 49	TL	**	223 B	STD	E-3	418	104.2	28.9	47.0	317.1	60	2815	19.50/4.0	-

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference