



## FORESTECH

### Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Forwarder



Version	STEEL BELTED
Tire Type	TL
Tyre size	710/45-26.5
LI/SS	168;A8

## Dimensions US Standard

USA Code	94029754
SW (US) (in)	28.0
OD (US) (in)	52.8
SLR (US) (in)	24.4
RC (US) (in)	159.3
Rim Rec	AG 24.00
ECE	E11-106R-003420
TRA Code	LS2

## Load Capacity (US)

mph / psi	73
25	12350
20	13200
5	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..