



EARTHMAX SR 45 H2



Description

EARTHMAX SR 45 H2 is an All Season tire designed for heavy-duty trucks. The E-4 tread depth and pattern are optimized for minimizing vibration and noise. It provides excellent traction and stability, even in wet conditions, and is resistant to snags and punctures and a long-lasting, cut-resistant compound.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	HEAT RESISTANT COMPOUND
Tire Type	TL
Tyre size	24.00R35
LI/SS	209;B

Dimensions IS Standard

OD (IS) (mm)	2180
SLR (IS) (mm)	978
RC (IS) (mm)	6597
Rim Rec	17.00/3.5
TRA Code	E4

Load Capacity (IS)

km/h / bar	05:00:00	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00	07:15:00	07:00:00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time v
or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or r
contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are prote
laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents,
format or otherwise without prior written consent by Balkrishna Industries Ltd..