



RIDEMAX FL 693 M



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tanker

Version	STANDARD
Tire Type	TL
Tyre size	600/50R22.5
LI/SS	159;D

Dimensions US Standard

USA Code	94037032
SW (US) (in)	24.1
OD (US) (in)	46.1
SLR (US) (in)	20.3
RC (US) (in)	140.7
Rim Rec	AG 20.00
ECE	E4-106R-000805

Load Capacity (US)

mph / psi	15	17	23	29	35	41	46	52	58
45	3260	3700	4500	5200	6000	6790	7320	8110	8820
40	3570	4060	4930	5700	6560	7430	8010	8870	9640
30	4320	4910	5960	6890	7950	8990	9690	10750	11670
25	4860	5510	6690	7750	8930	10110	10890	12070	13120
15	5640	6400	7780	8990	10370	11740	12650	14030	15240
5	6430	7300	8860	10250	11810	13370	14420	15970	17360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..