



AT 316

Description

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

IS Standard

Construction

◇◇ Bias

Machinery

Agriculture ■ Compact Utility Tractor



Version

STANDARD

Tire Type

TL

Tyre size

24x12.00-12

LI/SS

Dimensions IS Standard

SW (IS) (mm)	315
OD (IS) (mm)	610
SLR (IS) (mm)	271
RC (IS) (mm)	1769
Rim Rec	10.50 I - 55; I - 70; I - 90
ECE	E11-106R-004082

Load Capacity (IS)

km/h / bar	1.40
15	775

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..