



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 43



PRODUCT DATA SHEET



Radial



EARTHMAX SR 43

RADIAL OTR TIRES



EARTHMAX SR 43 is an All Steel radial tire specially designed for wheel loaders operating in severe rocky conditions, primarily underground mining. The tire delivers excellent performance in load and carry operations in open pit mines, quarries and scrap yards. Its unique tread design offers superior traction and stability. Thanks to its All Steel casing, EARTHMAX SR 43 provides excellent durability, resistance to snags and punctures as well as a long service life.

Technologies



All Steel

Performance



Traction



Hard Rocky Surface



Durability



Stability

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
															Rec.	Alt.
Ø 25"	94063291	29.5 R 25	TL	**	216 A2	CRC	L-4	-	73.8	30.9	33.3	222.2	77	1604	25.00/3.5	-
	94063390	29.5 R 25	TL	***	221 A2	CRC	L-4	-	73.8	30.9	33.3	222.2	77	1687	25.00/3.5	-
Ø 29"	94051021	29.5 R 29	TL	***	223 A2	CRC	L-4	-	78.9	30.2	35.6	237.4	78	1941	25.00/3.5	24.00/3.5 ; 26.00/3.5
	94071098	875/65 R 29 (35/65 R 29)	TL	***	228 A2	CRC	L-4	-	73.9	33.5	33.2	224.5	77	1995	27.00/3.5	27.00/3.0 ; 28.00/3.5
Ø 33"	94067312	35/65 R 33	TL	**	224 A2	CRC	L-4	-	81.7	35.4	37.7	252.4	77	2174	28.00/3.5	-
	94068869	35/65 R 33	TL	***	229 A2	CRC	L-4	-	81.7	35.4	37.7	252.4	77	2272	28.00/3.5	-
	94069910	35/65 R 33	TL	****	-	CRC	SH-4	-	81.7	35.4	37.7	252.4	77	2272	28.00/3.5	-
	94069903	35/65 R 33	TL	****/ ***	-	CRC	E-4/L-4	-	81.7	35.4	37.7	252.4	77	2272	28.00/3.5	-

CRC: Cut Resistant Compound

In case of underground mine application, consult your servicing dealer or BKT representative



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference