



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 425



PRODUCT DATA SHEET



Radial



EARTHMAX SR 425
RADIAL OTR TIRES

EARTHMAX SR 425 is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX SR 425 ensures excellent riding comfort, less driving fatigue and superior handling.

Technologies



Strong Casing



Steel Belted



All Steel

Performance



Durability



Handling and Comfort



High Load Capacity



Traction

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 24"	12.00 R 24	TT	-	20	160/156 K	STD	-	310	1230	564	3785	21	8.50	9.00
	12.00 R 24	TL	-	20	160/156 K	STD	-	310	1230	564	3785	21	8.50	9.00
	325/95 R 24	TT	-	20	160/156 K	STD	-	310	1230	564	3785	21	8.50	9.00
	NEWSIZE													
	325/95 R 24	TL	-	20	160/156 K	STD	-	310	1230	564	3785	21	8.50	9.00
	NEWSIZE													

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference