



RIB 713

Description

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The structure provides excellent puncture resistance and hence increased protection against stub penetration. "D" speed rating allows for fast road transfers.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Implement Machinery

Version STUBBLE RESISTANT

Tire Type TL

Tyre size IF265/85R15

LI/SS 121;D

Dimensions US Standard

USA Code	94053612
SW (US) (in)	10.2
OD (US) (in)	32.7
SLR (US) (in)	14.5
RC (US) (in)	98.5
Rim Rec	W 8
ECE	E11-106R-003956
TRA Code	I1

Load Capacity (US)

mph / psi	12	17	23	29	35
From 5 to 40 mph	1540	1980	2440	2790	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..