



## FLOTATION 648



### Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Baler

Version	DUAL BEAD
Tire Type	TL
Tyre size	600/50-22.5
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	611
OD (IS) (mm)	1170
SLR (IS) (mm)	510
RC (IS) (mm)	3501
Rim Rec	AG 20.00
ECE	E11-106R-004392

## Load Capacity (IS)

km/h / bar	3.00	3.10	3.20
10 FR	7820	7975	8120
20 FR	7035	7175	7310
30 FR	6255	6380	6495
40 FR	5585	5695	5800
50 FR	5025	5125	5150
10 DW	5390	5495	5600
20 DW	4850	4945	5040
30 DW	4310	4395	4480
40 DW	3850	3925	4000
50 DW	3465	3535	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..