



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 569



PRODUCT DATA SHEET



Radial



180



MULTIMAX MP 569
RADIAL MPT TIRES

🇬🇧 MULTIMAX MP 569 is a high-performance radial tire engineered for demanding industrial applications. MULTIMAX MP 569 is the ideal choice for equipping telehandlers and other construction equipment such as industrial tractors and excavators. The deep tread design, combined with wide shoulder lugs, ensures exceptional traction and flotation on multiple surfaces. The tire's All-Steel radial construction provides exceptional durability and superior resistance to punctures, significantly extending service life. Designed with angled directional lugs, the tread design facilitates effective self-cleaning, while the central tread blocks help maintain continuous ground contact, contributing to smooth roadability. This integrated tread design, featuring both center blocks and shoulder lugs, makes MULTIMAX MP 569 highly versatile and suitable for both on- and off-the-road applications.

Technologies



All Steel



High Speed

Performance



Traction



Self-Cleaning



Comfort



Low Rolling Resistance



Durability



Stability

	Tire size	LI/SS	RIM		O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 19.5"	445/70 R 19.5 (18 R 19.5)	173 A8/ 180 A2	14.00	-	453	1112	498	3363	-	STD
	NEWSIZE									
Ø 22.5"	445/65 R 22.5 (18 R 22.5)	169 J	13.00	14.00	440	1174	528	3558	-	STD

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index