



US standard



GROWING TOGETHER

MAGLIFT SMOOTH



PRODUCT DATA SHEET



Solid



MAGLIFT SMOOTH

MAGLIFT SMOOTH has been particularly designed for ground support equipment (GSE), port and industrial trailers operating on smooth surfaces. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and a long tire life. The smooth tread design and its maximum contact area provide extraordinary stability and optimized load distribution even under heavy-duty service conditions. MAGLIFT SMOOTH stands for excellent traction as well as low rolling resistance and low heat built up for improved efficiency. In addition, the specifically designed rim guard ensures protection against wheel damage, whilst the reinforced bead structure ensures best grip and eliminates any slippage risk during operations.

Technologies



Special Compound



Smooth Tire



Reinforced Bead

Performance



Cut and Chip Resistance



Stability



Traction



Low Rolling Resistance



Durability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 15"	94073061	300 - 15	-	-	-	STD	32.3	10.0	-	-	93	246	8.00 - 15	-
Ø 20"	94071210	10.00 - 20	-	-	-	STD	40.0	10.0	-	-	101	354	7.50 - 20	-
	94071227	10.00 - 20	-	-	-	STD	40.0	10.5	-	-	101	358	8.00 - 20	-
	94074006	11.00 - 20	-	-	-	STD	41.5	10.1	-	-	102	407	8.00 - 20	-
	94074013	11.00 - 20	-	-	-	STD	41.5	10.1	-	-	102	403	7.50 - 20	-
	94071241	12.00 - 20	-	-	-	STD	42.8	11.1	-	-	105	457	8.50 - 20	-
	94071234	12.00 - 20	-	-	-	STD	42.8	10.6	-	-	105	454	8.00 - 20	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference