



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF710/70R42
LI/SS	185;D

## Dimensions US Standard

USA Code	94066148
SW (US) (in)	28.1
OD (US) (in)	81.1
SLR (US) (in)	36.3
RC (US) (in)	243.4
Rim Rec	DW 25 B
Rim Alt	DW 23 B; DW 24 B
ECE	E11-106R-0010959

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
<b>45</b>	8730	10020	11510	13000	14470	15960	17450	18550
<b>From 40 to 25</b>	9590	11010	12640	14270	15910	17540	19170	20390
<b>20</b>	9780	11230	12900	14560	16230	17890	19550	20800
<b>12</b>	9980	11450	13150	14850	16540	18240	19940	21210
<b>5</b>	10550	12110	13910	15710	17500	19300	21090	22430
<b>*Upto 5 Cyc with front loader</b>	13430	15420	17700	19980	22280	24560	26840	28550
<b>5 HT</b>	9780	11230	12900	14560	16230	17890	19550	20800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..