



EARTHMAX SR 33



Description

EARTHMAX SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. The strong All Steel casing features excellent durability and resistance to snag and punctures.

UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	335/80R20
LI/SS	150;K

Dimensions IS Standard

OD (IS) (mm)	1047
SLR (IS) (mm)	464
RC (IS) (mm)	3145
Rim Rec	11
ECE	E11-54R-0016679

Load Capacity (IS)

km/h / bar	6.50
110	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..