



## AGRIMAX RT 765



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version SPECIAL

Tire Type TL

Tyre size 480/70R38

LI/SS 145;D

## Dimensions IS Standard

SW (IS) (mm)	479
OD (IS) (mm)	1681
SLR (IS) (mm)	764
RC (IS) (mm)	5055
Rim Rec	W 15 L
Rim Alt	W 14 L; W 16 L
ECE	E11-106R-005832
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6											
65	1595	1860	2120	2380	2640	2900											
50	1675	1950	2225	2500	2775	3045											
40	1750	2040	2325	2610	2895	3180											
30	1835	2135	2435	2735	3035	3335											
10 LT	2140	2490	2840	3190	3540	3890											
10 HT	1835	2135	2435	2735	3035	3335											

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..