



EARTHMAX SR 402



Description

EARTHMAX SR 402 (E-4) is an All Steel radial tire specifically engineered for longhaul dump trucks in mines and quarries. The unique tread design ensures reduced heat buildup and provides excellent traction and stability on all types of terrains and tracks where particular equipment control is a main requirement. The symmetrical, E-4-deep rock tread ensures easy fitment as well as excellent self-cleaning properties even in muddy conditions.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dumper

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	14.00R25
LI/SS	171;B

Dimensions IS Standard

OD (IS) (mm)	1385
SLR (IS) (mm)	644
RC (IS) (mm)	4261
Rim Rec	10.00/2.0
TRA Code	E4

Load Capacity (IS)

km/h / bar	7.00	8.00
50	5800	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..