



## SM 54 M IND-4S



### Description

SM 54 M IND-4S is a modified version of the SM 54 pattern. The flatter tread profile results in a large contact area ensuring a longer tire life-cycle. This tire has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. SM 54 M features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance.

### UM

IS Standard

### Construction

 Bias

### Machinery

Industrial & Construction ■ Reach Stacker

Version	PORT INDUSTRIAL
Tire Type	TL
Tyre size	18.00-33
LI/SS	

## Dimensions IS Standard

OD (IS) (mm)	1895
SLR (IS) (mm)	840
RC (IS) (mm)	5609
Rim Rec	13.00/2.5
TRA Code	IND-4S

## Load Capacity (IS)

km/h / bar	10.00
10	27000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..