



EARTHMAX SR 51



Description

EARTHMAX SR 51 (L-5) is an All Steel radial tire designed for use on wheel loaders or dozers. EARTHMAX SR 51 is ideal for applications requiring added cut resistance, sidewall protection, and superior traction. The extra deep tread ensures also extended tire life.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Dozer

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	17.5R25undefined
LI/SS	176;A2

Dimensions IS Standard

OD (IS) (mm)	1398
SLR (IS) (mm)	630
RC (IS) (mm)	4110
Rim Rec	14.00/1.5
TRA Code	L5

Load Capacity (IS)

km/h / bar	04:00:00	04:25:00	04:50:00	05:15:00	05:00:00															
10	6000	6150	6500	6700	7100															

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 22-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or omissions or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..