



RIB F3

Description

RIB F3 is a field-oriented tire designed for 2WD tractors in soil tillage and haulage operations. Some sizes are suitable for transport applications using trailers. The RIB F3 tire is the ideal partner for all operations that require a high level of handling. It has been designed with a hard compound to ensure great durability and stubble resistance.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ■ 2WD Tractor



Version	HD
Tire Type	TT
Tyre size	9.00-16
LI/SS	120;A6

Dimensions US Standard

USA Code	94042227
SW (US) (in)	9.6
OD (US) (in)	34.6
SLR (US) (in)	15.2
RC (US) (in)	101.3
Rim Rec	W 8
Rim Alt	6.00 F; W 7; W 8 L
ECE	E11-106R-004658
TRA Code	F3

Load Capacity (US)

mph / psi	68
20	3090
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..