



POWER TRAX HD (FL)

Description

POWER TRAX HD is a premium bias-ply tyre that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tyre features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.



UM

IS Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■

Version STANDARD

Tyre Type TT

Tyre size 27x10-12

LI/SS

Dimensions IS Standard

SW (mm)	255
OD (mm)	690
Rim Rec	8.00 G

Load Capacity (IS)

km/h / bar	10.00
25 LOAD WHEEL	4615
25 STEER WHEEL	3550
10 OTHER VEHICLES	4615
25 OTHER VEHICLES	3550
STATIC SIDE LOADER	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..