



FL 695

Description

FL 695 has been specifically designed for trailers in construction and farming transport applications with a unique center-block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions. Its deep tread ensures optimal self-cleaning during on-and-off-the-road applications. Multiple steel-cord layers reinforce this pattern against punctures.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Trailer, Industrial & Construction ■ Trailer



Version	STEEL BELTED
Tire Type	TL
Tyre size	600/60R30.5
LI/SS	179;D

Dimensions IS Standard

SW (IS) (mm)	611
OD (IS) (mm)	1495
SLR (IS) (mm)	693
RC (IS) (mm)	4586
Rim Rec	AG20.00
ECE	E11-106R-008503

Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	3490	4030	4575	5040	5505	6045	6435	6820	7285	7750
50	--	--	--	4225	4880	5535	6100	6660	7320	7790	8255	8820	9380
40	--	3480	4325	4745	5485	6220	6855	7485	8225	8750	9280	9910	10540
30	2930	3865	4800	5270	6090	6910	7610	8315	9130	9720	10305	11005	11705
25	3065	4045	5025	5515	6370	7225	7960	8695	9555	10165	10780	11515	12245
20	3200	4225	5245	5760	6655	7550	8315	9085	9980	10620	11260	12025	12790
10	3490	4605	5720	6280	7255	8235	9070	9905	10885	11580	12280	13115	13950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..