



IS standard



GROWING TOGETHER

SUPER GRADER



PRODUCT DATA SHEET



Bias



SUPER GRADER

SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

Technologies



Special Compound

Performance



Durability



Heavy Duty



Self-Cleaning



Traction

Ø 24"	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
13.00 - 24	TL	G-2	12	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC	
13.00 - 24	TL	G-2	16	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC	
13.00 - 24	TT	G-2	12	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC	
13.00 - 24	TT	G-2	16	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC	
14.00 - 24	TT	G-2	12	-	STD	-	364	1335	618	4037	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC; 10.00/VA SDC	
14.00 - 24	TT	G-2	16	-	STD	-	364	1335	618	4037	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC	
14.00 - 24	TL	G-2	12	-	STD	-	364	1335	618	4037	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC; 10.00/VA SDC	
14.00 - 24	TL	G-2	16	-	STD	-	364	1335	618	4037	25	8.00 TG SDC	9.00/1.5 (DC); 10.00/VA SDC; 10.00/VA SDC	
16.00 - 24	TL	G-2	16	-	STD	-	430	1450	644	4307	29	10.00 VA SDC	-	

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference