



## AGRIMAX PROHARVEST

### Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation.



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester

|           |              |
|-----------|--------------|
| Version   | STEEL BELTED |
| Tire Type | TL           |
| Tyre size | VF800/70R32  |
| LI/SS     | 187;D        |

## Dimensions US Standard

|               |                  |
|---------------|------------------|
| USA Code      | 94512263         |
| SW (US) (in)  | 31.7             |
| OD (US) (in)  | 76.1             |
| SLR (US) (in) | 33.3             |
| RC (US) (in)  | 229.0            |
| Rim Rec       | DW 28 B          |
| Rim Alt       | DW 27 B; DW 30 B |
| ECE           | E11-106R-0010664 |

## Load Capacity (US)

| mph / psi            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>45</b>            | 9180  | 10550 | 12110 | 13680 | 15240 | 16810 | 18370 | 19550 |
| <b>from 40 to 25</b> | 10100 | 11610 | 13330 | 15050 | 16770 | 18480 | 20200 | 21490 |
| <b>20</b>            | 10300 | 11840 | 13590 | 15340 | 17100 | 18850 | 20600 | 21920 |
| <b>12</b>            | 10500 | 12070 | 13860 | 15640 | 17430 | 19220 | 21010 | 22350 |
| <b>5</b>             | 11110 | 12760 | 14650 | 16540 | 18440 | 20330 | 22220 | 23640 |
| <b>Upto 20 Cyc</b>   | 11460 | 13170 | 15120 | 17070 | 19020 | 20980 | 22930 | 24390 |
| <b>Upto 10 Cyc</b>   | 13680 | 15720 | 18050 | 20380 | 22710 | 25040 | 27370 | 29120 |
| <b>Upto 5 Cyc</b>    | 14990 | 17230 | 19770 | 22330 | 24890 | 27440 | 29990 | 31910 |
| <b>10HT</b>          | 10300 | 11840 | 13590 | 15340 | 17100 | 18850 | 20600 | 21920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..