



US standard



GROWING TOGETHER

LOADER PLUS



PRODUCT DATA SHEET



Bias



LOADER PLUS

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.

Performance



Cut Resistance



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94064915	14.00 - 25	TT	20	-	STD	L-3	-	53.9	14.8	24.8	159.4	33	257	10.00/1.5	-
	94064939	17.5 - 25	TT	16	-	STD	L-3	-	53.0	17.3	24.5	156.7	33	242	14.00/1.5	-
	94064946	17.5 - 25	TL	16	-	STD	L-3	-	53.0	17.3	24.5	156.7	33	254	14.00/1.5	-
	94064953	17.5 - 25	TT	20	-	DB	L-3	-	53.0	17.3	24.5	156.7	33	262	14.00/1.5	-
	94064960	20.5 - 25	TT	16	-	STD	L-3	-	58.7	21.3	27.0	173.6	37	380	17.00/2.0	-
	94064977	20.5 - 25	TL	16	-	STD	L-3	-	58.7	21.3	27.0	173.6	37	401	17.00/2.0	-
	94064984	20.5 - 25	TT	20	-	STD	L-3	-	58.7	21.3	27.0	173.6	37	403	17.00/2.0	-
	94064991	20.5 - 25	TL	20	-	STD	L-3	-	58.7	21.3	27.0	173.6	37	424	17.00/2.0	-
	94065004	23.5 - 25	TT	16	-	STD	L-3	-	64.6	24.0	29.5	191.1	41	487	19.50/2.5	-
	94065011	23.5 - 25	TL	16	-	STD	L-3	-	64.6	24.0	29.5	191.1	41	509	19.50/2.5	-
	94065042	23.5 - 25	TL	24	-	STD	L-3	-	64.6	24.0	29.5	191.1	41	561	19.50/2.5	-
	94065028	23.5 - 25	TT	20	-	STD	L-3	-	64.6	24.0	29.5	191.1	41	516	19.50/2.5	-
	94065035	23.5 - 25	TL	20	-	STD	L-3	-	64.6	24.0	29.5	191.1	41	533	19.50/2.5	-
	94065066	26.5 - 25	TL	32	-	STD	L-3	-	68.5	26.8	31.3	202.8	46	786	22.00/3.0	-
	94065059	26.5 - 25	TL	28	-	STD	L-3	-	68.5	26.8	31.3	202.8	46	757	22.00/3.0	-
	94065080	29.5 - 25	TL	32	-	STD	L-3	-	73.2	29.9	33.4	218.3	49	980	25.00/3.5	-
	94065073	29.5 - 25	TL	28	-	STD	L-3	-	73.2	29.9	33.4	218.3	49	948	25.00/3.5	-

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference