



IS standard



GROWING TOGETHER

COMMANDER 3 RIB



PRODUCT DATA SHEET



Bias



Technologies



Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



COMMANDER 3 RIB

🇬🇧 COMMANDER 3 RIB is a 3-rib pattern front tire designed for soil tillage and haulage operations. It provides excellent durability and load capacity thanks to the optimized weight distribution on center and shoulder ribs. The strong casing along with the cut-and-chip resistant compound ensure outstanding puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	6.00 - 16	4.50 E	4.00 E ; 5.00 F	175	740	-	-	STD	8	TT	94A6
	6.00 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	765	-	-	STD	8	TT	98A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	212	810	-	-	STD	8	TT	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference