



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 25 PLUS



PRODUCT DATA SHEET



Radial

G-2/L-2



A8

175

Technologies



All Steel

Performance



Traction



Self-Cleaning



Durability



# EARTHMAX SR 25 PLUS

RADIAL OTR TIRES

EARTHMAX SR 25 PLUS (G-2/L-2) is an All Steel radial tire, which has been specially designed for motor graders and loaders operating in the most severe road construction or mining applications. Its non-directional tread design offers excellent self-cleaning properties in addition to traction and stability off the road.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 24"	14.00 R 24	TL	G-2/L-2	*	153 A8/ 175 A2	CRC	-	359	1372	626	4146	25	8.00 TG	9.00 GR

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference