



IS standard



GROWING TOGETHER

# FLOTATION 647



PRODUCT DATA SHEET



Bias



159

**Performance**



Self-Cleaning



Traction



# FLOTATION 647

FLOTATION 647 is an implement tire that features best traction on soft soil and grassland. In addition to excellent self-cleaning properties, the specially designed tread pattern provides a wide contact area, which ensures optimized ground pressure and excellent performance on soft soil.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 15.3"	260/75 - 15.3	9.00	-	275	785	363	2380	STD	-	TL	119 A8	131 A8
Ø 17"	380/55 - 17	13.00	-	385	882	-	-	STD	-	TL	125 A8	138 A8
	<b>NEWSIZE</b> 520/50 - 17	AG 16.00	-	516	965	426	2907	STD	-	TL	147 B	159 B
Ø 18"	425/70 - 18	13.00	-	435	1065	-	-	STD	-	TL	143 B	155 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling