



## FLOTATION 648



### Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

### UM

IS Standard

### Construction

### Machinery

Agriculture ■ Baler

Version	STANDARD
Tire Type	TL
Tyre size	600/55-22.5
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	600
OD (IS) (mm)	1230
SLR (IS) (mm)	540
RC (IS) (mm)	3716
Rim Rec	AG 20.00
ECE	E4-106R-001564

## field\_1

km/h / bar	02:20:00	02:40:00	03:00:00																
10 FR	7365	7750	8120																
20 FR	6630	6975	7310																
30 FR	5890	6200	6495																
40 FR	5260	5535	5800																
50 FR	4735	4980	5300																
10 DW	5080	5340	5600																
20 DW	4575	4805	5040																
30 DW	4065	4275	4480																
40 DW	3630	3815	4000																
50 DW	3265	3435	3650																

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are

protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..